

AMI-GLAS 1000° FIBERGLASS TAPE

PART NO:	THICKNESS	WIDTH / LENGTH
GL16-1	.060"	1" / 100 FT
GL16-1.5	.060"	1.50" / 100 FT
GL16-2	.060"	2" / 100 FT
GL16-3	.060"	3" / 100 FT
GL16-4	.060"	4" / 100 FT
GL16-6	.060"	6" / 100 FT
GL08-1	.125"	1" / 50 FT
GL08-1.5	.125"	1.50" / 50 FT
GL08-2	.125"	2" / 50 FT
GL08-3	.125"	3" / 50 FT
GL08-4	.125"	4" / 50 FT
GL08-6	.125"	6" / 50 FT



DELIVERY: 3 - 5 DAYS A.R.O

OTHER THICKNESSES and WIDTHS AVAILABLE

- Made with 100% continuous filament fiberglass
- Continuous protection up to 1000° F (540° C)
- Excellent insulation value (K=.419)
- Tough, flexible and versatile
- Meets USCG 164.009 for incombustibility
- Non-hazardous to workers
Meets military specifications for shipbuilding and repair
- Can be dyed, coated and/or aluminized
- Available with pressure-sensitive adhesive
- Can be slit or sewn to order, and specially packaged

ALSO AVAILABLE IN:

- CLOTH
- TADPOLE
- ROPE
- BLANKETS

Used for Welding Protection, Insulation, Gasketing, Expansion Joints, Heat Shields and Containment, Oven Door Seals, Emergency Fire Blanket and Machinery, Personnel Protection, Safety Clothing and more.

AMI-SIL 1800° TAPE

PART NO:	THICKNESS	WIDTH / LENGTH
AS50-1	.050"	1" / 100 FT
AS50-1.5	.050"	1.50" / 100 FT
AS50-2	.050"	2" / 100 FT
AS50-3	.050"	3" / 100 FT
AS50-4	.050"	4" / 100 FT
AS50-6	.050"	6" / 100 FT
AS90-1	.090"	1" / 50 FT
AS90-1.5	.090"	1.50" / 50 FT
AS90-2	.090"	2" / 50 FT
AS90-3	.090"	3" / 50 FT
AS90-4	.090"	4" / 50 FT
AS90-6	.090"	6" / 50 FT



1. MINIMUM ORDER: 1 ROLL
2. DELIVERY: 3-5 DAYS A.R.O

- Continuous protection to 1800°F (1000°C)
- Melting point in excess of 3000°F (1650°C)
- Minimum 96% amorphous silica content
- Meets military specification MIL-C-24576
- Flexible and chemical resistant
- Low thermal conductivity

Low halogens and soluble chlorides
AVAILABLE WITH ADHESIVE BACK-PLEASE

- SPECIFY WITH ADHESIVE BACK WHEN REQUESTING A QUOTE

AVAILABLE IN:

