

LOCKING WINDOW GASKETS

ONE PIECE LOCKING GASKETS

<p>1/4" Glass</p> <p>1/16" Edge</p> <p>LK-1522 100 ft and 50 ft</p>	<p>1/4" Glass</p> <p>1/8" Edge</p> <p>LK-1663 200 ft and 50 ft</p>	<p>1/4" Glass</p> <p>1/8" Edge</p> <p>LK-987 100 ft and 50 ft</p>	<p>1/4" Glass</p> <p>1/4" Edge</p> <p>LK-1536 100 ft and 50 ft</p>																																																								
<p>1/4" Glass</p> <p>1/16" Edge</p> <p>LK-1615 100 ft and 50 ft</p>	<p>1/4" Glass</p> <p>1/16" Edge</p> <p>LK-1621 200 ft and 50 ft</p>	<p>1/4" Glass</p> <p>1/8" Edge</p> <p>LK-1660 100 ft and 50 ft</p>																																																									
	<table border="1"> <thead> <tr> <th>Part Number</th> <th>Glass Panel Thickness</th> <th>Body panel thickness</th> <th>Minimum recommended clearance between glass and edge</th> <th>Overall Height</th> <th>Minimum recommended radius of panel opening</th> <th>Weight per foot</th> </tr> </thead> <tbody> <tr> <td>LK-1522</td> <td>0.1875" - .250"</td> <td>0.035" - 0.067"</td> <td>0.3125"</td> <td>1.07"</td> <td>2.5"</td> <td>0.275 lbs.</td> </tr> <tr> <td>LK-1663</td> <td>0.1875" - .250"</td> <td>0.09" - 0.14"</td> <td>0.25"</td> <td>0.9"</td> <td>1.5"</td> <td>0.196 lbs.</td> </tr> <tr> <td>LK-987</td> <td>0.1875" - .250"</td> <td>0.09" - 0.14"</td> <td>0.3125"</td> <td>1.07"</td> <td>2.5"</td> <td>0.246 lbs.</td> </tr> <tr> <td>LK-1536</td> <td>0.1875" - .250"</td> <td>0.1875" - 0.25"</td> <td>0.406"</td> <td>1.09"</td> <td>3.5"</td> <td>0.225 lbs.</td> </tr> <tr> <td>LK-1615</td> <td>0.1875" - .250"</td> <td>0.06" - 0.09"</td> <td>0.3125"</td> <td>0.906"</td> <td>2.5"</td> <td>0.275 lbs.</td> </tr> <tr> <td>LK-1621</td> <td>0.1875" - 0.250"</td> <td>0.046" - 0.075"</td> <td>0.125"</td> <td>0.937"</td> <td>2.0"</td> <td>0.26 lbs.</td> </tr> <tr> <td>LK-1660</td> <td>0.1875" - 0.250"</td> <td>0.075" - 0.140"</td> <td>0.145"</td> <td>1.00"</td> <td>2.00"</td> <td>0.293 lbs.</td> </tr> </tbody> </table>	Part Number	Glass Panel Thickness	Body panel thickness	Minimum recommended clearance between glass and edge	Overall Height	Minimum recommended radius of panel opening	Weight per foot	LK-1522	0.1875" - .250"	0.035" - 0.067"	0.3125"	1.07"	2.5"	0.275 lbs.	LK-1663	0.1875" - .250"	0.09" - 0.14"	0.25"	0.9"	1.5"	0.196 lbs.	LK-987	0.1875" - .250"	0.09" - 0.14"	0.3125"	1.07"	2.5"	0.246 lbs.	LK-1536	0.1875" - .250"	0.1875" - 0.25"	0.406"	1.09"	3.5"	0.225 lbs.	LK-1615	0.1875" - .250"	0.06" - 0.09"	0.3125"	0.906"	2.5"	0.275 lbs.	LK-1621	0.1875" - 0.250"	0.046" - 0.075"	0.125"	0.937"	2.0"	0.26 lbs.	LK-1660	0.1875" - 0.250"	0.075" - 0.140"	0.145"	1.00"	2.00"	0.293 lbs.		
Part Number	Glass Panel Thickness	Body panel thickness	Minimum recommended clearance between glass and edge	Overall Height	Minimum recommended radius of panel opening	Weight per foot																																																					
LK-1522	0.1875" - .250"	0.035" - 0.067"	0.3125"	1.07"	2.5"	0.275 lbs.																																																					
LK-1663	0.1875" - .250"	0.09" - 0.14"	0.25"	0.9"	1.5"	0.196 lbs.																																																					
LK-987	0.1875" - .250"	0.09" - 0.14"	0.3125"	1.07"	2.5"	0.246 lbs.																																																					
LK-1536	0.1875" - .250"	0.1875" - 0.25"	0.406"	1.09"	3.5"	0.225 lbs.																																																					
LK-1615	0.1875" - .250"	0.06" - 0.09"	0.3125"	0.906"	2.5"	0.275 lbs.																																																					
LK-1621	0.1875" - 0.250"	0.046" - 0.075"	0.125"	0.937"	2.0"	0.26 lbs.																																																					
LK-1660	0.1875" - 0.250"	0.075" - 0.140"	0.145"	1.00"	2.00"	0.293 lbs.																																																					

TWO PIECE LOCKING GASKETS – PART 1



LOCKING KEY – PART 2

Installed Profile Example	Part Number	Glass Panel Thickness	Body panel thickness	Minimum recommended clearance between glass and edge	Overall Height	Minimum recommended radius of panel opening	Weight per foot	Matching lockstrip part number (part 2)
<p>Two Piece Locking Gasket Part 1</p> <p>Lock Strip Part 2</p>	LK-1035	0.1875" - .250"	0.050" - .095"	0.23"	0.85"	2.25"	0.155 lbs.	LK-937
	LK-1179	0.1875" - .250"	0.093" - .140"	0.3"	1.10"	2.5"	0.277 lbs.	LK-937
	LK-1488	0.1875" - .250"	0.1875" - .250"	0.3"	1.00"	3.5"	0.202 lbs.	LK-937
	LK-1456	0.1875" - .250"	0.175" - .188"	0.3"	0.95"	2.0"	0.198 lbs.	LK-937
	LK-1696	0.1375" - .250"	0.175" - .188"	0.3"	0.95"	2.0"	0.193 lbs.	LK-937



SAN DIEGO SEAL, INC.

7635 RONSON ROAD • SAN DIEGO, CALIFORNIA 92111

TEL: 858-278-3270 • FAX: 858-278-2950

E-MAIL: sales@sandiegoseal.com • VISIT US AT: www.sandiegoseal.com