

TYPE 87 NYLON INSERTED NEOPRENE

COLOR: BLACK

FEATURES: A SPECIAL NEOPRENE COMPOUND WITH A MEDIUM WEIGHT WOVEN NYLON INSERT FOR MAXIMUM STRENGTH.

EQUIPMENT: CONTROL VALVES AND ALL EQUIPMENT APPLICATIONS WHERE A DIAPHRAGM MATERIAL IS REQUIRED.

LIMITATIONS: TEMPERATURES -20°F TO 180°F



REMARKS: NEOPRENE SHEET AND A NYLON CLOTH ARE COMBINED FOR THE ADVANTAGED OF OIL AND FUEL RESISTANCE OF THE NEOPRENE AND THE ADDITIONAL STRETCH AND STRENGTH OF THE NYLON.

Hardness	60 Shore A +/-5
Tensile	1000 PSI
Elongation	400%
Finish	Smooth
Test Method	Mullen Burst Test Rating Over 1000psi with 1" Square Opening
High Strength	Tear Resistant, Meets ASTM D2000 Type BC

Thickness	PART NUMBER: 36" WIDE	PART NUMBER: 48" WIDE
1/16"	SDS-06236-NI	SDS-06248-NI
3/32"	SDS-09336-NI	SDS-09348-NI
1/8"	SDS-12536-NI	SDS-12548-NI
3/16"	SDS-18736-NI	SDS-18748-NI
1/4"	SDS-25036-NI	SDS-25048-NI