

## Low Pressure Nylon Expansion Plugs Sizes 0.5" to 6"



These superior, versatile, expandable plugs are used to accommodate a wide variety of industrial applications where an airtight seal is required.

### **Advantages:**

- Quality, Lightweight, Durable Nylon 20% lighter than metal.
- Tough/shatter-proof and easily cleaned and maintained, corrosion resistant.
- Plaster or cement do not adhere to the plug.
- Friction-reducing acetyl copolymer thrust washer inserted between plate and wing nut provides for easy expansion.
- Natural Rubber provides "superior" seal.
- Larger sizes incorporate strengthening ribs to provide rigidity in use.
- Silicon, nitrile, and viton seals available

<b>Solid Stem / SS-0.50" to 1.50"</b>				
<b>Item Number</b>	<b>Nominal Size</b>	<b>Size Unexpanded</b>	<b>Size Expanded</b>	<b>Unit Weight (LBS.)</b>
<b>SS0.50</b>	0.50"	0.490"	0.600"	1/4
<b>SS0.75</b>	0.75"	0.740"	0.900"	1/4
<b>SS1.00</b>	1.00"	0.975"	1.200"	1/4
<b>SS1.25</b>	1.25"	1.225"	1.450"	1/4
<b>SS1.50</b>	1.50"	1.480"	1.750"	1/4
<b>***SS series now available with vented stem</b>				

<b>HOLLOW STEM / VS-0.50" TO 6"</b>				
<b>Item Number</b>	<b>Nominal Size</b>	<b>Size Unexpanded</b>	<b>Size Expanded</b>	<b>Unit Weight (LBS.)</b>
<b>VS0.50</b>	0.50"	0.490"	0.600"	1/4
<b>VS0.75</b>	0.75"	0.740"	0.900"	1/4
<b>VS1.00</b>	1.00"	0.975"	1.200"	1/4
<b>VS1.25</b>	1.25"	1.225"	1.450"	1/4
<b>VS1.50</b>	1.50"	1.420"	1.930"	1/4
<b>VS2.00</b>	2.00"	1.930"	2.360"	1/4
<b>VS2.50</b>	2.50"	2.400"	2.760"	1/4
<b>VS3.00</b>	3.00"	2.870"	3.310"	1/3
<b>VS4.00</b>	4.00"	3.540"	4.250"	1/2
<b>VS5.00</b>	5.00"	4.720"	5.370"	1
<b>VS6.00</b>	6.00"	5.500"	6.290"	1



**SAN DIEGO SEAL, INC.**

7635 RONSON ROAD • SAN DIEGO, CALIFORNIA 92111

TEL: 858-278-3270 • FAX: 858-278-2950

E-MAIL: sales@sandiegoseal.com • VISIT US AT: www.sandiegoseal.com