

HYPALON (CHLOROSULFONATED POLYETHELENE)

FEATURES: RESISTS GOOD ACID, ALKALI AND SALT RESISTANCE, OILS AND COMMERCIAL FUELS SUCH AS DIESEL AND KEROSENE. IT RESISTS WEATHERING, SUNLIGHT AND OZONE.

LIMITATIONS: TEMPERATURES FROM -50°F TO 275°F.

HYPALON IS NOT GOOD IN AROMATICS OR CHLORINATED HYDROCARBONS AND HAS POOR RESISTANCE AGAINST CHROMIC ACID AND NITRIC ACID.

RED RUBBER

COLOR: RED

FEATURES: A GENERAL SERVICE SBR RUBBER COMPOUND OF EXCELLENT QUALITY. THIS HEAT RESISTANT MATERIAL HAS BEEN CALENDERED AND VULCANIZED UNDER THE STRICTEST CONTROL.

EQUIPMENT: ALL MATING FLANGES WHEREVER A QUALITY RUBBER SHEET IS REQUIRED.

REMARKS: DEFORMS TO UNEVEN FLANGES.

OPERATING TEMPERATURE: -20°F TO +170°F



PURE GUM

COLOR: TAN

FEATURES: A COMPOSITION OF SPECIALLY BLENDED COMPOUNDS. SOFT, PLIABLE, CAPABLE OF FILLING FLANGE IRREGULARITIES WITH THE LIGHTEST BOLT LOADS.

SURFACE: SMOOTH

EQUIPMENT: ALL MATING FLANGES.

LIMITATIONS: TEMPERATURES TO 200°F / 93°C.

REMARKS: DEFORMS EASILY AND RECOVERS READILY.

